

BlueTruckMaster® AdBlue® Storage & Dispensing Solutions Product Guide

Available from 200 – 900 litres



Portable AdBlue® Storage & Dispensing Solutions

Available from 200 – 900 litres

The BlueTruckMaster range has been specifically designed for the safe transportation of diesel fuel. This robust, portable solution offers users the ultimate convenience by allowing them to refuel remotely on-site.

Available from 200 – 900 litres, with a number of specification and dispensing options, the BlueTruckMaster range suits a variety of applications including agricultural, construction, forestry, transport and logistics. Built from high-quality polyethylene all tanks are resistant to structural damage, changing weather conditions and UV radiation. The Kingspan BlueTruckMaster range offers a quality, cost saving and compliant solution backed by excellent technical and customer service support.

BTM430/300 Equipment Specification

1. Tank
2. Pump
3. Automatic nozzle
4. Vent
5. Delivery hose
6. Lockable lid***
7. Shackles†
8. Filling offset†††



BlueTruckMaster®



Standard Equipment

- Semi-transparent PE tank with internal partition
- Locked lid
- Gas cylinders to facilitate the opening of the lid*
- Suction tube equipped with a filter to ensure the cleanliness of the liquid
- Self-priming pump 12V DC
- 13ft dispensing hose with automatic nozzle
- Automatic air purge valve
- Threaded inlet connection

Quality Design and Reliability

The BlueTruckMaster is built from high quality polyethylene providing resistance to structural damage, changing weather conditions and UV radiation whilst offering a number of equipment options to suit all types of user.

Excellent Return on Investment

Lightweight, portable storage solution offering a faster and safer delivery of AdBlue® to any point of use and model options which occupy only half a euro pallet – saving you valuable time and money.

Portability & Design Features

The BlueTruckMaster has been designed to go anywhere and to withstand the toughest of site conditions offering liquid delivery a new mobility. Additionally, the unique internal baffle wall minimises spillage when in transit - protecting AdBlue® and the environment.

Optional Equipment

- Self-priming pump 24V DC
- Digital flow meter to control the amount of liquid dispensed
- LED lighting powered by a battery to make it easier to use at night
- Lifting shackles
- Manual nozzle



Key features:

- Specialised tank design enables installation on a vehicle using transporting straps
- Integrated bulkhead to reduce movement of transported liquid
- Closable cover to protect tank equipment and armature against unauthorised access
- Integrated pump to allow instant filling
- Automatic filling nozzle to protect against spills during refuelling
- Ability to deliver AdBlue® to target location
- Wide range of pumps to accommodate various power supply options,
- 5 year tank guarantee and 2 years on parts
- After-warranty service
- The highest quality components designed for long-term AdBlue® storage

* Option available only on BTM900 model
** 5 year tank guarantee and 2 years on equipment

Model Selector

All dimensions and weights are an approximate only

* 200 and 300 models do not require ADR approval due to their smaller capacity
** One year on equipment
*** Lid with integrated lock (BTM200 Low Profile, 430 & 900).
Lid with lockable latch, padlock not provided (BTM200 and BTM300)
† Available on BTM200 Low Profile, BTM430 & BTM900
†† Available on BTM200, BTM300 and BTM200 Low Profile
††† Available in different options BTM430 & BTM900

BTM200



Capacity	200 litres
Length	600 mm
Width	800 mm
Height	620 mm
Weight	33 kg

BTM200 low profile



Capacity	200 litres
Length	1180 mm
Width	860 mm
Height	500 mm
Weight	52 kg

BTM300



Capacity	300 litres
Length	600 mm
Width	800 mm
Height	890 mm
Weight	45 kg

BTM430



Capacity	430 litres
Length	1180 mm
Width	860 mm
Height	910 mm
Weight	64 kg

BTM900



Capacity	900 litres
Length	1410 mm
Width	1050 mm
Height	1210mm
Weight	97 kg

Specification Selector

Data sheets are available for each of the specification options below

BlueTruckMaster®

DESCRIPTION / CAPACITY	BTM200	BTM200 LOW PROFILE	BTM300	BTM430	BTM900
Ball valve on suction line				•	•
Suction line with mesh filter	•	•	•	•	•
12 V DC pump (max. flow rate 50 l/min)	•	•	•	•	•
6 m power cable with battery clamps	•	•	•	•	•
4 m flexible delivery hose	•		•		
Automatic nozzle		•		•	•
Lid with integrated lock	•	•	•	•	•
Lid with lockable latch (padlock not provided)		•		•	•
Vacuum and pressure relief valve (VENT)	•		•		
Lid with support gas struts	•	•	•	•	•
4 lifting shackles				○	○
Battery powered LED lamp		○		○	○
24 V DC pump (max. flow rate 50 L/min)		○		○	○
230 V AC pump (max. flow rate 56 L/min)	○	○	○	○	○
Digital flowmeter fixed to the nozzle	○	○	○	○	○

- Standard accessories ○ Optional accessories



SHUBHAM ACQUALINK (INDIA) PVT. LTD.
(Formerly known as Tanclean Pvt Ltd)

128, Lodha Supremus II, North Wing,
Road No.22, Wagle Industrial Estate,
Thane - 400 604,
MAHARASHTRA, INDIA.

T: +91 22 49748989
M: +91 98191 96593
shubhamacqualink.com



We take every care to ensure that the information in this document is accurate at the point of publication, but with continuous product development, details are subject to alteration without notice.

3138_ROW_BTМ_Generic_EN

Working Together